



Lexmark XM5370

Output of up to 66 ppm* and a standard hard disk help the flexibly configurable, OCR-equipped Lexmark XM5370 monochrome multifunction product to meet large-workgroup needs.

Part Number

25B1291

Print Technology

Black & White Laser Printer

Function

Colour Scanning, Copying, Faxing, Network Scanning, Printing

Workgroup Size

Large Workgroup

Touch Screen Display

Yes

Display

Lexmark e-Task 7-inch (17.8 cm) colour touch screen

Print Speed (A4, Black)

Up to 66 ppm⁶

Print Speed (A4, Black) Duplex

Up to 40 spm⁶

Time to First Page (Black)

As fast as 4.0 seconds

Duplex (2-sided) Printing

Integrated Duplex

Print Resolution, Black

1200 IQ (1200 x 600 dpi), 1200 x 1200 dpi, 2400 IQ (2400 x 600 dpi), 300 x 300 dpi, 600 x 600 dpi

Copy Speed (A4, Black)

Up to 66 cpm⁶

Copy Speed (A4, Black) Duplex

Up to 42 spm⁶

Time to First Copy (Black)

As fast as 4.0 seconds

Reduce / Enlarge Range

25 - 400 %

A4/Ltr Simplex Scan Speed (Black)

Up to 72 / 75 sides per minute

Scan Speed (A4/Ltr, Colour)

Up to 72 / 75 sides per minute

A4/Ltr Duplex Scan Speed (Black)

Up to 144 / 150 sides per minute

Duplex Scan Speed (A4/Ltr, Colour)

Up to 144 / 150 sides per minute

Scan Area, Maximum (mm)

215.9 x 355.6 mm

ADF Scan

DADF (single pass Duplex)

Scanner Type

Flatbed scanner with ADF

Scan Technology

CCD

Optical Scanning Resolution

600 X 600 dpi (black), up to 600 X 600 dpi (colour)

Scan File Formats (Send as)

JPEG, JPG, PDF, Secure PDF, TIFF, Archival PDF (A-1a, A-1b), Searchable PDF

Scan Destinations

e-mail, FTP, USB Flash drive, USB or Network connected computer, Lexmark Document Solutions Suite (LDSS)

Modem Speed

Max is 33,600 bps, V.34 Half-Duplex Kbps

Fax Transmission Speed

< 3 seconds per page

Processor Speed

Quad Core, 1.2 GHz

Memory, Standard

2 GB

Memory, Maximum

6 GB

Hard Disk

Included in configuration

Apple Operating Systems Supported

Support is provided through AirPrint and AirScan only

Citrix MetaFrame

Microsoft Windows Server 2012 R2 Datacenter Edition running Citrix XenApp 7.5, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16, Microsoft Windows Server 2012 Datacenter Edition running Citrix XenApp 7.5, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16, Microsoft Windows Server 2012 Foundation running Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 Essentials running Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 Standard running Citrix XenApp 6.0, 6.5

Linux Operating Systems Supported

Ubuntu 20.04, Debian 10, SUSE Linux Enterprise Server 12 SP5, OpenSUSE 15.2, Debian 11, Ubuntu 22.04, Fedora 36, Fedora 37, SUSE Linux Enterprise Server 15 SP4, OpenSUSE 15.4, Red Hat Linux 8.7, Red Hat Linux 9.1

Microsoft Windows Operating Systems Supported

Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows Server 2012, Windows 8.1, Windows Server 2012 R2, Windows 10, Windows Server 2016, Windows Server 2019, Windows Server 2022, Windows 11

Novell Operating Systems Supported

Novell NetWare 6.5 Open Enterprise Server 3, Novell Open Enterprise Server 2 (SP3) on SuSE Linux Enterprise Server 10 SP4 (x86 and x64) 3, Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64), Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 12 SP1 (x86 and x64), Novell Open Enterprise Server 15 (SP1) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64)

Included Paper Handling

550-Sheet Input, 100-Sheet Multipurpose Feeder, 550-Sheet Output Bin, Integrated Duplex

Optional Paper Handling

250-Sheet Tray, 550-Sheet Tray, 2100-Sheet Tray, 250-Sheet Lockable Tray, 550-Sheet Lockable Tray

Paper Input Capacity, Standard

Up to 650 pages 75 gsm bond

Paper Input Capacity, Maximum

Up to 3300 pages 75 gsm bond

Paper Output Capacity, Standard

Up to 550 pages 75 gsm bond

Paper Output Capacity, Maximum

Up to 550 pages 75 gsm bond

Paper Weight Range Supported - Standard Tray (gsm)

60 - 176 gsm

Integrated Tray Card Stock Upper limit (grain short)

Cover - 176 gsm (65 lb), Index Bristol - 199 gsm (110 lb), Tag - 203 gsm (125 lb)

ADF

200-Sheet Automatic Document Feeder

ADF Paper Input Capacity

Up to 200 pages 75 gsm bond

ADF Paper Output Capacity

Up to 200 pages 75 gsm bond

Finishing Option

No

Number of Paper Inputs, Standard

2

Number of Paper Inputs, Maximum

5

Media Types Supported

Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Transparencies, Refer to the Paper & Specialty Media Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

Caster Base

Optional

Standard Ports

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear USB 2.0 Specification Hi-Speed Certified port (Type A)

Optional Local Ports

Internal RS-232C serial, Internal 1284-B Bidirectional Parallel

Optional Network Ports

Marknet N8370 WiFi Option, MarkNet N8230 Fiber Ethernet Print Server, Marknet N8372 WiFi Option

Direct USB

Yes

Ethernet Network

Yes

Network Protocol Support

TCP/IP IPv4, TCP/IP IPv6, TCP, UDP

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Enhanced IP (Port 9400), Secure IP (Port 96xx), FTP, TFTP, ThinPrint .print integration, Telnet, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD, Pull Printing

Network Management Protocols¹

HTTP, HTTPS (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, Telnet, Finger,

Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPsec

Printable Area (metric)

4.2 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 5e Emulation, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, AirPrint™, PDF 1.7 emulation

Fonts and Symbol Sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 158 scalable PostScript fonts, 2 PCL bitmap fonts, 39 scalable PPDS fonts, 5 PPDS bitmap fonts, 84 scalable PCL fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference.

Laser Cartridge Yields (up to)⁵

45,000-page Extra High Yield Cartridge,

Imaging Unit Estimated YieldUp to 150000 pages, based on 5 average letter/A4 size pages per print job and ~ 5% coverage for CS/CX96x, CX83x, CX95x, and MX95x printer series, or based on 3 average letter/A4 size pages per print job and ~ 5% coverage for all other printers⁴**Cartridge(s) Shipping with Product**

11,000-page Return Program Toner Cartridge

Replacement Cartridges:Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.**Packaged Size (mm - H x W x D)**

1020 x 700 x 735 mm

Packaged Weight, kg

58.6 kg

Size (mm - H x W x D)

739.1 x 558.8 x 578.4 mm

Weight

44.1 kg

Noise Level, Idle

14 dBA

Noise Level (Print), Operating

57 dBA

Duplex Print Noise Level, Operating

57 dBA

Noise Level (Copy), Operating

60 dBA

Noise Level (Scan), Operating

56 dBA

Quiet Mode

53 dBA

ENERGY STAR

Yes

Average Power (Hibernate Mode)

0.2 watts

Average Power (Sleep Mode)

2.0 watts

Average Power (Ready Mode)

42 watts

Average Power (Printing)

850 watts

Average Power while Printing Duplex

640 watts

Average Power (Copying)

890 watts

Average Power (Scanning)

73 watts

ENERGY STAR Typical Electricity**Consumption (TEC)**

3.3 kilowatt-hours per week

Product Warranty**Product Certifications**

ENERGY STAR, Blue Angel RAL-UZ 205, ICES-003 Class A, BSMI Class A, VCCI Class A, US FDA/CDRH, UL 60950-1, FCC Class A, cUL CAN/CSA-C22.2 60950-1, NOM, MET-I, IEC 60825-1, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CCD-035, CE DoC (EN 62301 Class A, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class A, EuP, EN 55024, UL), EFTA (CE), CISPR 22 Class A, KCC, CCC, CECF, CEL, A-tick DoC, C-tick CoC, UL-AR, KC mark, UL GS mark, ISO 532B, ECMA-370, TED, GOST-R, SII, TER, Bel GISS

Maximum Monthly Duty CycleUp to 350000 pages per month³**Recommended Monthly Page Volume**5000 - 100000 pages²**Specified Operating Environment**

Humidity: 8 to 80% Relative Humidity, Temperature: 10 to 32°C, Altitude: 0 - 2896 metres


License/Agreement TermsPrinters are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.**Country of Origin**

China (PRC)

UNSPSC Code

43212110

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.⁵Average yield at approximately 5% print coverage per colour.⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.



Callout	Availability	Description
1	Standard	17.8 cm Touch Screen
10	Optional	Swivel Cabinet
11	Optional	Adjustable Stand
12	Optional	Spacer
2	Standard	100-Sheet Multipurpose Feeder
3	Standard	550-Sheet Input
4	Optional	550-Sheet Tray
5	Optional	550-Sheet Tray
6	Optional	Caster Base
7	Optional	250-Sheet Tray
8	Optional	550-Sheet Lockable Tray
9	Optional	250-Sheet Lockable Tray

P/N Toner Cartridges

25B3074 Lexmark M5255, 5270, XM5355,
5370, 7355, 7365, 7370 45K Toner
Cartridge

P/N Paper Handling

50G0800 250-Sheet Tray
50G0801 250-Sheet Tray
50G0820 250-Sheet Lockable Tray
50G0802 550-Sheet Tray
50G0803 550-Sheet Tray Insert
50G0822 550-Sheet Lockable Tray
50G0804 2100-Sheet Tray
50G0854 4.3 in. (11 cm) Spacer

P/N Furniture

40C2300 Adjustable Stand
50G0855 Caster Base
3073173 Swivel Cabinet

P/N Memory Options

27X0400 500+ GB Hard Disk
57X9801 256MB Flash Memory Card
57X9814 Korean Font Card
57X9815 Japanese Font Card
57X9812 Simplified Chinese Font Card
57X9810 Traditional Chinese Font Card
57X0204 4GBx32 DDR3-DRAM

P/N Application Solutions

40C9201 Card for IPDS
40C9200 Forms and Bar Code Card
40C9202 Card for PRESCRIBE Emulation
57X0300 Contact Authentication Device
57X0301 Contactless Authentication Device
(Secondary Alternative)
57X0210 Elatec Reader Authentication Device
57X0250 Elatec TWN4 MultiTech-P LEGIC 42
Kit Bosch-SPR000264

P/N Connectivity

27X0142 Lexmark MarkNet™ N8230 Fiber
Ethernet Print Server
27X6410 Lexmark MarkNet N8372 802.11 a/b/
g/n/ac Wireless Print Server
27X6510 MarkNet N8370 802.11 a/b/g/n/ac
Wireless Print Server
1021231 Parallel (10') Cable
1021294 USB (2 Metre) Cable
14F0100 RS-232C Serial Interface Card
14F0000 Parallel 1284-B Interface Card

P/N Extended Warranties

2363007 XM5370 1-Year Renewal Parts Only
Etended Warranty w/ Kits
2363017 XM5370 4-Years Total (1+3) Onsite
Service w/ Kits
2363019 XM5370 1-Year Onsite Service
Renewal w/ Kits
2366652 XM5370 2-Year Onsite Service
Renewal w/ Kits
2366656 XM5370 2-Year Renewal Parts Only
Etended Warranty w/ Kits