



# Lexmark XM7355

Designed for speed and uptime, the Lexmark XM7355 features monochrome output of up to 52 ppm\*, long-life imaging components and Ultra High Yield toner capacity.

<b>Part Number</b>		<b>Scan File Formats (Send as)</b>	
25B1297		JPEG, JPG, PDF, Secure PDF, TIFF, Archival PDF (A-1a, A-1b), Searchable PDF	
<b>Print Technology</b>		<b>Scan Destinations</b>	
Black & White Laser Printer		e-mail, FTP, USB Flash drive, USB or Network connected computer, Lexmark Document Solutions Suite (LDSS)	
<b>Function</b>		<b>Modem Speed</b>	
Colour Scanning, Copying, Faxing, Network Scanning, Printing		Max is 33,600 bps, V.34 Half-Duplex Kbps	
<b>Workgroup Size</b>		<b>Fax Transmission Speed</b>	
Large Workgroup		< 3 seconds per page	
<b>Touch Screen Display</b>		<b>Processor Speed</b>	
Yes		Quad Core, 1.2 GHz	
<b>Display</b>		<b>Memory, Standard</b>	
Lexmark e-Task 10.1-inch (25.6 cm) colour touch screen		2048 MB	
<b>Print Speed (A4, Black)</b>		<b>Memory, Maximum</b>	
Up to 52 ppm <sup>6</sup>		6144 MB	
<b>Print Speed (A4, Black) Duplex</b>		<b>Hard Disk</b>	
Up to 32 ppm <sup>6</sup>		Included in configuration	
<b>Time to First Page (Black)</b>		<b>Apple Operating Systems Supported</b>	
As fast as 4.5 seconds		Support is provided through AirPrint and AirScan only	
<b>Duplex (2-sided) Printing</b>		<b>Citrix MetaFrame</b>	
Integrated Duplex		Microsoft Windows Server 2012 R2 Datacenter Edition running Citrix XenApp 7.5, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16, Microsoft Windows Server 2012 Datacenter Edition running Citrix XenApp 7.5, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16, Microsoft Windows Server 2012 Foundation running Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 Essentials running Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 Standard running Citrix XenApp 6.0, 6.5	
<b>Print Resolution, Black</b>		<b>Linux Operating Systems Supported</b>	
1200 IQ (1200 x 600 dpi), 1200 x 1200 dpi, 2400 IQ (2400 x 600 dpi), 300 x 300 dpi, 600 x 600 dpi		Ubuntu 20.04, Debian 10, SUSE Linux Enterprise Server 12 SP5, OpenSUSE 15.2, Debian 11, Ubuntu 22.04, Fedora 36, Fedora 37, SUSE Linux Enterprise Server 15 SP4, OpenSUSE 15.4, Red Hat Linux 8.7, Red Hat Linux 9.1	
<b>Copy Speed (A4, Black)</b>		<b>Microsoft Windows Operating Systems Supported</b>	
Up to 52 cpm <sup>6</sup>		Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows Server 2012, Windows 8.1, Windows Server 2012 R2, Windows 10, Windows Server 2016, Windows Server 2019, Windows Server 2022, Windows 11	
<b>Copy Speed (A4, Black) Duplex</b>		<b>Novell Operating Systems Supported</b>	
Up to 33 cpm <sup>6</sup>		Novell NetWare 6.5 Open Enterprise Server 3, Novell Open Enterprise Server 2 (SP3) on SuSE Linux Enterprise Server 10 SP4 (x86 and x64) 3, Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64), Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 12 SP1 (x86 and x64), Novell Open Enterprise Server 15 (SP1) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64)	
<b>Time to First Copy (Black)</b>		<b>Caster Base</b>	
As fast as 4.5 seconds		Included	
<b>Reduce / Enlarge Range</b>		<b>Standard Ports</b>	
25 - 400 %		One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear USB 2.0 Specification Hi-Speed Certified port (Type A)	
<b>A4/Ltr Simplex Scan Speed (Black)</b>		<b>Optional Local Ports</b>	
Up to 72 / 75 sides per minute		Internal RS-232C serial, Internal 1284-B Bidirectional Parallel	
<b>Scan Speed (A4/Ltr, Colour)</b>		<b>Optional Network Ports</b>	
Up to 72 / 75 sides per minute		Marknet N8370 WiFi Option, MarkNet N8230 Fiber Ethernet Print Server, Marknet N8372 WiFi Option	
<b>A4/Ltr Duplex Scan Speed (Black)</b>			
Up to 144 / 150 sides per minute			
<b>Duplex Scan Speed (A4/Ltr, Colour)</b>			
Up to 144 / 150 sides per minute			
<b>Scan Area, Maximum (mm)</b>			
215.9 x 355.6 mm			
<b>ADF Scan</b>			
DADF (single pass Duplex)			
<b>Scanner Type</b>			
Flatbed scanner with ADF			
<b>Scan Technology</b>			
CCD			
<b>Scan Resolution, Enhanced</b>			
(Flatbed, Mono) Up to 1200 x 1200 dpi; (ADF) Up to 600 x 600 dpi			
<b>Scan Resolution, Optical</b>			
Up to 1200 dpi (Flatbed); Up to 600 dpi (ADF)			

<b>Direct USB</b>	
Yes	
<b>Ethernet Network</b>	
Yes	
<b>Network Protocol Support</b>	
TCP/IP IPv4, TCP/IP IPv6, TCP, UDP	
<b>Network Printing Methods</b>	
LPR/LPD, Direct IP (Port 9100), Enhanced IP (Port 9400), FTP, TFTP, ThinPrint .print integration, Telnet, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol)	
<b>Network Management Protocols<sup>1</sup></b>	
HTTP, HTTPS (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, Telnet, Finger,	
<b>Network Security</b>	
SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec	
<b>Printable Area (metric)</b>	
4.2 mm of the top, bottom, right and left edges (within)	
<b>Printer Languages (Standard)</b>	
PCL 5e Emulation, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, AirPrint™, PDF 1.7 emulation	
<b>Fonts and Symbol Sets</b>	
3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 158 scalable PostScript fonts, 2 PCL bitmap fonts, 39 scalable PPDS fonts, 5 PPDS bitmap fonts, 84 scalable PCL fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference.	
<b>Laser Cartridge Yields (up to)<sup>5</sup></b>	
45,000-page Extra High Yield Cartridge,	
<b>Imaging Unit Estimated Yield</b>	
Up to 150000 pages, based on 5 average letter/A4 size pages per print job and ~ 5% coverage for CS/CX96x, CX83x, CX95x, and MX95x printer series, or based on 3 average letter/A4 size pages per print job and ~ 5% coverage for all other printers <sup>4</sup>	
<b>Cartridge(s) Shipping with Product</b>	
11,000-page Return Program Toner Cartridge	
<b>Replacement Cartridges:</b>	
Product functions only with replacement cartridges designed for use in a specific geographical region. See <a href="http://www.lexmark.com/">www.lexmark.com/</a> regions for more details.	
<b>Packaged Size (mm - H x W x D)</b>	
1365 x 762 x 830 mm	
<b>Packaged Weight, kg</b>	
101.2 kg	
<b>Size (mm - H x W x D)</b>	
1150.6 x 685.8 x 693.4 mm	
<b>Weight</b>	
67.0 kg	
<b>Noise Level, Idle</b>	
14 dBA	
<b>Noise Level (Print), Operating</b>	
54 dBA	
<b>Duplex Print Noise Level, Operating</b>	
53 dBA	
<b>Noise Level (Copy), Operating</b>	
58 dBA	
<b>Noise Level (Scan), Operating</b>	
57 dBA	
<b>Quiet Mode</b>	
50 dBA	

<b>ENERGY STAR</b>	
Yes	
<b>Average Power (Hibernate Mode)</b>	
0.2 watts	
<b>Average Power (Sleep Mode)</b>	
3.1 watts	
<b>Average Power (Ready Mode)</b>	
58 watts	
<b>Average Power (Printing)</b>	
690 watts	
<b>Average Power while Printing Duplex</b>	
490 watts	
<b>Average Power (Copying)</b>	
750 watts	
<b>Average Power (Scanning)</b>	
84 watts	
<b>ENERGY STAR Typical Electricity Consumption (TEC)</b>	
2.4 kilowatt-hours per week	
<b>Product Warranty</b>	
<b>Product Certifications</b>	
ENERGY STAR, Blue Angel RAL-UZ 205, ICES-003 Class A, BSMI Class A, VCCI Class A, US FDA/CDRH, UL 60950-1, FCC Class A, cUL CAN/CSA-C22.2 60950-1, NOM, MET-I, IEC 60825-1, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CCD-035, CE DoC (EN 62301 Class A, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class A, EuP, EN 55024, UL), EFTA (CE), CISPR 22 Class A, KCC, CCC, CECP, CEL, A-tick DoC, C-tick CoC, UL-AR, KC mark, UL GS mark, ISO 532B, ECMA-370, TED, GOST-R, SII, TER, Bel GISS	
<b>Maximum Monthly Duty Cycle</b>	
Up to 300000 pages per month <sup>3</sup>	
<b>Recommended Monthly Page Volume</b>	
3000 - 50000 pages <sup>2</sup>	
<b>Specified Operating Environment</b>	
Humidity: 8 to 80% Relative Humidity, Temperature: 10 to 32°C, Altitude: 0 - 2896 metres	
<b>License/Agreement Terms</b>	
Printers are sold subject to certain license/agreement conditions. See <a href="http://www.lexmark.com/">www.lexmark.com/</a> printerlicense for details.	
<b>Country of Origin</b>	
China (PRC)	
<b>UNSPSC Code</b>	
43212110	

<sup>1</sup>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)

<sup>2</sup>"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

<sup>3</sup>"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

<sup>4</sup>Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

<sup>5</sup>Average yield at approximately 5% print coverage per colour.

<sup>6</sup>Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).



Callout	Availability	Description
1	Standard	
10	Optional	4-Bin Mailbox
11	Optional	Offset Stackers
2	Standard	100-Sheet Multipurpose Feeder
3	Standard	550-Sheet Tray
4	Standard	
5	Standard	Caster Base
6	Optional	
7	Optional	Staple Punch Finisher
8	Optional	Staple Finisher
9	Optional	Keyboard

<b>P/N</b>	<b>Toner Cartridges</b>
25B3086	Lexmark XM7355, 7365, 7370 45K Toner Cartridge
25A0013	Staple Cartridges (3 pack)

<b>P/N</b>	<b>Paper Handling</b>
50G0801	250-Sheet Tray
25B2900	550-Sheet Tray
25B2950	2100-Sheet Tray
25B2999	500-Sheet Offset Stacker
50G0849	Staple, Hole Punch Finisher
50G0850	Staple Finisher
50G0852	4-Bin Mailbox

<b>P/N</b>	<b>Memory Options</b>
57X9801	256MB Flash Memory Card
57X9814	Korean Font Card
57X9815	Japanese Font Card
57X9812	Simplified Chinese Font Card
57X9810	Traditional Chinese Font Card
57X0204	4GBx32 DDR3-DRAM

<b>P/N</b>	<b>Application Solutions</b>
40C9201	Card for IPDS
40C9200	Forms and Bar Code Card
40C9202	Card for PRESCRIBE Emulation
57X0300	Contact Authentication Device
57X0301	Contactless Authentication Device (Secondary Alternative)
57X0210	Elatec Reader Authentication Device
57X0250	Elatec TWN4 MultiTech-P LEGIC 42 Kit Bosch-SPR000264

<b>P/N</b>	<b>Connectivity</b>
27X0142	Lexmark MarkNet™ N8230 Fiber Ethernet Print Server
27X6410	Lexmark MarkNet N8372 802.11 a/b/ g/n/ac Wireless Print Server
27X6510	MarkNet N8370 802.11 a/b/g/n/ac Wireless Print Server
57X7030	English Keyboard Kit
57X7040	English Keyboard Kit
1021231	Parallel (10') Cable
1021294	USB (2 Metre) Cable
14F0100	RS-232C Serial Interface Card
14F0000	Parallel 1284-B Interface Card

<b>P/N</b>	<b>Extended Warranties</b>
2363025	XM7355 2-Years Total (1+1) Base Onsite Service
2363026	XM7355 3-Years Total (1+2) Base Onsite Service
2363027	XM7355 2-Years Total (1+1) Onsite Service
2363028	XM7355 3-Years Total (1+2) Onsite Service